


Cricket[™]

More than a Pipe Buggy!

- ✓ Transport 20 ft (6.1 m) pipe lengths up to 1,000 Lb. (450 Kg)
- ✓ Comes with ratchet hold-down strap and 16" tubed or flat free tires.
- ✓ Weighs only 70 Lb (31.8 Kg)... can be shipped U.P.S.
- ✓ Quick handle disconnect for compact storage.
- ✓ Carries up to 12" diameter pipe.
- ✓ Ideal job-site material carrier.



Now available with flat free tires!



Patented

Great for flanges, fittings and valves

Uses leverage to lift pipe!



1 use ratchet to secure Cricket to pipe



2 use handle to flip Cricket & pipe



3 reposition handle



Part No.	Description	Height		Width		Width between Wheels		Length		Weight	
		inch	cm	inch	cm	inch	cm	inch	cm	Lb	Kg
782699	Cricket	21	53	28	71	16	41	28	71	70	33
782685	Cricket with flat free tires	21	53	28	71	16	41	28	71	70	33

SUMNER®



MAG RACK



Patent Pending

A Mobile Conduit & Pipe Storage Rack!

- ✓ Double wall square tubing
- ✓ Eight bins of storage
- ✓ Arms fold easily with plunger pins
- ✓ 6" Heavy duty casters *standard* with each Mac Rack
- ✓ Powder coat finish
- ✓ Priced for all budgets

SPECIFICATIONS	With Casters		Without Casters	
	inch	cm	inch	cm
Height Stowed	17.75	45.0	10.5	26.6
Height Operating	61.5	155.6	53.75	136.5
Length	58.5	148.6	58.5	148.6
Width	33.0	83.8	33.0	83.8
Ground clearance	7.5	19.1	—	—
Weight	145 lb	65.9 kg	117 lb	53.2 kg

Part No.	Description	Weight	
		Lb	Kg
783317	Mac Rack complete with two 6" swivel casters and two 6" straight casters	145	65.9



Support masts nest into base by pulling plunger pins. Masts fold up in seconds – no loose hardware or tools required.



Base design is compact and allows users to stack Mac Rack and Pipe Mac (see page 30) carts.



A great transporter of pipe, strut, hanging rod, conduit, etc.

Grasshopper

Texas Pipe Dolly

Enables one man to lift 2,000 lb (900 Kg) unassisted!



- ✓ Special sliding chain block design accommodates long and short loads
- ✓ Carries up to 20" diameter pipe, tool boxes, fittings and valves

Now shipped on a convenient pallet requiring only 15 minutes for assembly.

GRASSHOPPER SPECIFICATIONS						LOAD CAPACITY											
Part No.	Description	Weight		Length		Width		Height		Weight	Length	Width	Height				
		lb	kg	ft.	cm	in.	cm	in.	cm					lb	kg	ft.	cm
780351	ST-401 Grasshopper	155	70.0	12	366	35	89	40	102	2,000	900	20	610	20	51	28	71

PIPE MAC™

A Mobile Pipe Cart

- ✓ Transports 2,000 lb (900 Kg) of pipe, individually or up to a height of 34" (86 cm)
- ✓ Six 6" Heavy duty casters
- ✓ Center-positioned casters makes rolling the Pipe Mac easy and enables quick cart rotation for tight turns
- ✓ Posts pull out for compact storage
- ✓ Stacks when not in use

New!



Compact storage



Pipe Mac comes with vee attachment. Shown transporting 20" pipe




Pipe Mac stacks with other Pipe Macs or with Mac Racks (see page 29).

SPECIFICATIONS	inch	cm
Height (stowed)	19.5	49.5
Height (operating)	44.0	111.7
Length	58.5	148.6
Width	33.0	83.8
Ground clearance	7.5	19.1
Post Height	34.0	86.4

Vee Attachment included!

Simple but rugged attachment prevents pipe from rolling while the Pipe Mac is in motion.

Easily slips over the four post holders —no tools required!



Part No.	Description	Weight	
		Lb	Kg
783230	Pipe Mac	150.0	68.2



WELDING CYLINDER CARTS

Sumner offers a full range of cylinder carts, shown on pages 31–34. See page 35 for specifications, wheel information is on page 36.



Small Single Cylinder Cart (Model #108)

Designed to transport small cylinders up to 8-1/4" (21 cm) diameter. Perfect for moving acetylene "B" tanks or fire extinguishers around job sites. Comes with 8" rubber wheels and safety chain.

cart part number 782375
108-8S Safety Chain
Wheels Shown: 779024*



Heavy Duty, Single Cylinder Cart (Model #112)

Popular cylinder truck can be used for gas cylinders up to 12" (30 cm) in diameter or for hauling boxes on the 7 x 14" (17.8 x 35.6 cm) base plate. Load capacity rated at 500 lb (225 Kg).

cart part number 782385
112-10S Safety Chain
Wheels Shown: 779011*
cart part number 782386
112-10P Safety Chain
Wheels Shown: 779027*



Small-Medium Range, High Rail Cylinder Carts (Models #207 & #208)

The small-medium range cylinder carts feature a balanced design for comfortable handling on smooth, level surfaces. Carts come with trays and hose hooks. Handle grips offer better control and stability.

cart part number 782360
207-8S Safety Chain
Wheels Shown: 779029*

cart part number 782359
207-10S Safety Chain
Wheels Shown: 779011*

base plate: 7.5 x 15.5" (19.0 x 39.4 cm)



cart part number 782379
208-8S Safety Chain
Wheels Shown: 779029*

cart part number 782380
208-10S Safety Chain
Wheels Shown: 779011*

base plate: 8.0 x 17.0" (20.3 x 43.2 cm)

* See page 36 for wheel information.

Medium Range, High Rail Cylinder Cart (Model #209)

Ideal for handling two tanks (a 244–330 cu ft oxygen and a 145 cu ft acetylene 9-1/4" diameter tank). High rail design contains cylinders while moving about job sites. This cart comes with 9 x 18" (22.9 x 45.7 cm) base plate and a large, open tool tray as standard equipment. Options include safety chain or steel containment bar and a range of wheels.



cart part number 782420
209-10S Safety Chain
Wheels Shown: 779011*



cart part number 782422
209-10P Safety Chain
Wheels Shown: 779027*



cart part number 782424
209-14S Safety Chain
Wheels Shown: 779028*



cart part number 782426
209-16P Safety Chain
Wheels Shown: 779107*



cart part number 782421
209-10SB Steel
Containment Bar
Wheels Shown: 779011*



cart part number 782423
209-10PB Steel
Containment Bar
Wheels Shown: 779027*



cart part number 782425
209-14SB Steel
Containment Bar
Wheels Shown: 779028*



cart part number 782427
209-16PB Steel
Containment Bar
Wheels Shown: 779107*



cart part number 782428
209-16F Safety
Chain, & Flat Free
Tires
Wheels Shown: 779104*



cart part number 782441
209-14SB-L Lifting
Eye**, Divider Wall &
Double Containment
Bars
Wheels Shown: 779028*



cart part number 782443
209-16PB-LF Lifting
Eye**, Firewall*** &
Double Containment
Bars
Wheels Shown: 779107*



cart part number 782444
209-16FB-LF Lifting
Eye**, Firewall***,
Double Containment
Bars & Flat Free Tires
Wheels Shown: 779104*

Full Range, High Rail Cylinder Cart (Model #213)

The high rail feature secures tanks on to the cart while moving around job site situations. Full range cart holds one 244–330cu ft (9-1/4") oxygen tank and one 210–420 cu ft (13-1/2") acetylene tank. Equipped with 13 x 25" (33 x 63 cm) base plate and a large, open tool tray standard equipment. Options include safety chain or steel containment bar and a range of wheels.



cart part number 782480
213-14S Safety Chain
Wheels Shown: 779028*



cart part number 782482
213-16P Safety Chain
Wheels Shown: 779107*



cart part number 782481
213-14SB Steel
Containment Bar
Wheels Shown: 779028*



cart part number 782483
213-16PB Steel
Containment Bar
Wheels Shown: 779107*



cart part number 782484
213-16F Safety Chain
& Flat Free Tires
Wheels Shown: 779104*

New!



cart part number 782493
213-14SB-L Lifting
Eye**, Divider Wall &
Double Containment
Bars
Wheels Shown: 779028*



cart part number 782491
213-14SB-LF Lifting
Eye**, Firewall*** &
Double Containment
Bars
Wheels Shown: 779028*



cart part number 782495
213-16PB-LF Lifting
Eye**, Firewall*** &
Double Containment
Bars
Wheels Shown: 779107*



cart part number 782496
213-16FB-LF Lifting
Eye**, Firewall***,
Double Containment
Bars & Flat Free Tires
Wheels Shown: 778104*

New!



cart part number 782497
213-25PB-LF Lifting
Eye**, Firewall*** &
Double Containment
Bars
Wheels Shown: 780521*

New!

Medium and Full Range
Cylinder Cart specifications
are on page 35.

* See page 36 for wheel
information.


** Lifting eye carts comply
with ASME B30.20,
AWS D14.1 and AISC
codes.

*** Fire-rated wall complies
with OSHA 1926.350 &
OSHA 1910.253.

Cylinder-to-Cart Cross Reference




Use this guide to select the Sumner welding cylinder cart that best matches your needs! (Cylinders not sold.)




For
40 cu. ft. acetylene and 50 to 80 cu. ft. oxygen
cylinders, chose

Model #108 or #207 Cylinder Carts (page 31)




For
75 cu. ft. acetylene and 80 to 150 cu. ft. oxygen
cylinders, chose

Model #112 or #208 Cylinder Carts (page 31)



For
145 cu. ft. acetylene and 244 to 330 cu. ft. oxygen (K,H,T)
cylinders, chose

Model #112 or #209 Cylinder Carts (pages 31 and 32)




For
210 to 420 cu. ft. acetylene and 244 to 330 cu. ft. oxygen (K,H,T)
cylinders, chose

Model #213 Cylinder Carts (page 33)

How to read Sumner Cylinder Cart product descriptions

X X X - X X X X - X X



EXAMPLE: cart part number 782496, 213-16FB-LF

- 2 = carries two cylinders
- 13 = 13 inch maximum cylinder diameter
- 16 = 16 inch wheel size
- F = Flat free tire
- B = Belly bar
- L = Lifting eye
- F = Firewall

Single Cylinder Carts (Models #108 & #112)

Part No.	Description	Dimensions			Weight	
		Height	Depth	Width	Lb	Kg
782375	108-8S Cylinder Cart	40.0" (101.6 cm)	12.3" (31.2 cm)	12.1" (30.7 cm)	12.0	5.5
782385	112-10S Cylinder Cart	49.4" (125.5 cm)	18.0" (45.7 cm)	19.1" (48.6 cm)	36.0	16.4
782386	112-10P Cylinder Cart	49.4" (125.5 cm)	18.1" (46.0 cm)	20.8" (52.8 cm)	28.0	12.7

Small Double Cylinder Carts (Models #207 & #208)

Part No.	Description	Dimensions			Weight	
		Height	Depth	Length	Lb	Kg
782360	207-8S Cylinder Cart	41.0" (104.1 cm)	21.8" (55.2 cm)	12.8" (32.3 cm)	35.0	15.9
782359	207-10S Cylinder Cart	41.0" (104.1 cm)	22.8" (57.8 cm)	13.8" (34.9 cm)	35.0	15.9
782379	208-8S Cylinder Cart	49.5" (125.7 cm)	22.0" (55.9 cm)	18.3" (46.4 cm)	42.0	19.1
782380	208-10S Cylinder Cart	49.5" (125.7 cm)	23.0" (58.4 cm)	18.3" (46.4 cm)	42.0	19.1

Double Cylinder Carts (Models #209 & #213)

Part No.	Description	Dimensions			Weight	
		Height	Depth	Width	Lb	Kg
782420	209-10S Cylinder Cart w/Chain	43.6" (110.7 cm)	16.9" (42.9 cm)	28.0" (71.0 cm)	48.0	21.8
782421	209-10SB Cylinder Cart w/Bar	43.6" (110.7 cm)	16.9" (42.9 cm)	28.0" (71.0 cm)	49.0	23.3
782422	209-10P Cylinder Cart w/Chain	43.6" (110.7 cm)	16.9" (42.9 cm)	29.0" (75.2 cm)	40.0	18.2
782423	209-10PB Cylinder Cart w/Bar	43.6" (110.7 cm)	16.9" (42.9 cm)	29.0" (75.2 cm)	41.0	18.6
782424	209-14S Cylinder Cart w/Chain	43.6" (110.7 cm)	16.9" (42.9 cm)	28.0" (71.0 cm)	47.0	21.4
782425	209-14SB Cylinder Cart w/Bar	43.6" (110.7 cm)	16.9" (42.9 cm)	28.0" (71.0 cm)	48.0	21.8
782426	209-16P Cylinder Cart w/Chain	43.6" (110.7 cm)	18.27" (46.4 cm)	32.5" (82.6 cm)	53.0	24.1
782427	209-16PB Cylinder Cart w/Bar	43.6" (110.7 cm)	18.27" (46.4 cm)	32.5" (82.6 cm)	54.0	24.5
782428	209-16F Cylinder Cart w/Chain	43.6" (110.7 cm)	18.27" (46.4 cm)	32.5" (82.6 cm)	53.0	24.1
782480	213-14S Cylinder Cart w/Chain	44.6" (113.3 cm)	20.3" (51.6 cm)	31.8" (80.8 cm)	53.0	24.0
782481	213-14SB Cylinder Cart w/Bar	44.6" (113.3 cm)	20.3" (51.6 cm)	31.8" (80.8 cm)	55.0	25.0
782482	213-16P Cylinder Cart w/Chain	44.6" (113.3 cm)	22.1" (56.1 cm)	36.5" (92.7 cm)	59.0	26.8
782483	213-16PB Cylinder Cart w/Bar	44.6" (113.3 cm)	22.1" (56.1 cm)	36.5" (92.7 cm)	61.0	27.7
782484	213-16F Cylinder Cart w/Chain	44.6" (113.3 cm)	22.1" (56.1 cm)	36.5" (92.7 cm)	59.0	26.8

Double Cylinder Carts with Lifting Eye and/or Fire Wall (Models #209 & #213)

Part No.	Description	Dimensions			Weight	
		Height	Depth	Width	Lb	Kg
782441	209-14SB-L Cylinder Cart w/Divider	66.0" (167.6 cm)	17.0" (43.2 cm)	27.5" (69.9 cm)	69.0	31.3
782443	209-16PB-LF Cylinder Cart w/Firewall	66.0" (167.6 cm)	18.4" (46.7 cm)	32.4" (82.3 cm)	75.5	34.2
782444	209-16FB-LF Cylinder Cart w/Firewall	66.0" (167.6 cm)	18.4" (46.7 cm)	32.4" (82.3 cm)	74.0	33.6
782491	213-14SB-LF Cylinder Cart w/Firewall	66.5" (168.9 cm)	20.5" (52.1 cm)	31.8" (80.8 cm)	100.0	45.5
782493	213-14SB-L Cylinder Cart w/Divider	66.5" (168.9 cm)	20.5" (52.1 cm)	31.8" (80.8 cm)	84.0	38.1
782495	213-16PB-LF Cylinder Cart w/Firewall	66.5" (168.9 cm)	22.1" (56.1 cm)	36.8" (93.5 cm)	109.0	49.4
782496	213-16FB-LF Cylinder Cart w/Firewall	66.5" (168.9 cm)	22.1" (56.1 cm)	36.8" (93.5 cm)	108.0	49.1
782497	213-25PB-LF Cylinder Cart w/Firewall	66.5" (168.9 cm)	27.1" (68.8 cm)	36.8" (93.5 cm)	152.0	69.1

Welding Cylinder Cart Wheel List

Sumner cylinder carts come equipped with high quality wheels as specified below the photos on pages 31 through 33. The chart below lists wheel specifications and the carts on which they can be used.

Part No.	Diameter	Width	Bore	Bearing	Description	Load Capacity	Fits Sumner Cart(s)
779024	8"	1.75"	1/2"	Powder metal bushing	Semi-pneumatic	80 lb	108, 207, 208
779029	8"	2.00"	1/2"	Powder metal bushing	Semi-pneumatic	800 lb	207, 208
779011	10"	2.75"	5/8"	Bronze bushing	Semi-pneumatic	400 lb	112, 209, 207, 208
779027	10"	3.5"	5/8"	Bronze bushing	Pneumatic	350 lb	112, 209
779028	14"	1.75"	5/8"	Bronze bushing	Semi-pneumatic	150 lb	209, 213
779104	16"	4.8"	1"	Powder metal bushing	Flat free	380 lb	209, 213
779107	16"	4.8"	1"	Powder metal bushing	Pneumatic	380 lb	209, 213
780521	25"	4"	1 1/4"	Bronze bushing	Pneumatic	800 lb	213



Sumner Manufacturing Co., Inc.

7514 Alabonson Road
Houston, Texas 77088

voice: (281) 999-6900
fax: (281) 999-6966

In Canada: 470 Collier MacMillan Drive, Unit 2 & 3
Cambridge, ON N1R 5Y7

voice: (519) 623-2300
fax: (519) 623-0744

In the UK: Unit 16A
Blackpole Trading Estate East
Blackpole Road
Worcester
WR3 8SG, UK

voice: (44) 01905 458333
fax: (44) 01905 458222

www.sumner.com