

ELECTRODE HOLDERS

ELECTRODE HOLDERS

"AF" Series



"HT" Series



Part No	Description	Amp capacity	Cable capacity	Electrodes up to	Length
"AF" Series					
AF2	Light duty	200 - 250	1/0 (50mm ²)	5/32" (3.97mm)	8 1/4" (210mm)
AF25	Medium duty	250 - 300	2/0 (70mm ²)	3/16" (4.75mm)	8 1/2" (216mm)
AF35	Heavy duty	350 - 400	3/0 (70mm ²)	1/4" (6.35mm)	10" (254mm)
AF50		450 - 500	4/0 (95mm ²)	3/8" (9.53mm)	10 1/2" (267mm)

"HT" Series					
HT2	Light duty	200 - 250	1/0 (50mm ²)	5/32" (3.97mm)	9" (229mm)
HT25	Medium duty	250 - 300	2/0 (70mm ²)	3/16" (4.75mm)	9 3/4" (248mm)
HT35	Heavy duty	350 - 400	3/0 (70mm ²)	1/4" (6.35mm)	10 1/2" (267mm)
HT50		450 - 500	4/0 (95mm ²)	3/8" (9.53 mm)	10 1/2" (267 mm)

DURO ELECTRODE HOLDER

- Unique design
- No coil spring to lose its tension



Part No	Description	Amp capacity	Cable capacity	Electrodes up to	Length
L016600	Heavy duty	600	4/0 (95mm ²)	3/8" (9.5mm)	13-1/4" (337mm)

TWISTER ELECTRODE HOLDER



Part No	Description	Amp capacity	Cable capacity	Electrodes up to	Length
LT250	Medium duty	250	2/0 (70mm ²)	3/16" (4.75mm)	8" (203mm)
LT400	Heavy duty	400	3/0 (70mm ²)	1/4" (6.35mm)	8-15/16" (227mm)

PROGRESS HOLDER

Recognized worldwide for the special design of the head. When changing electrodes no live (metal) parts are exposed.

Part No	Description
V010341100	Electrode Progress Holder 400-1
V010360100	Electrode Progress Holder 600-1



OPTIMUS HOLDER

Optimus is a high quality electrode holder, with a closed head. The wide range of welding applications with optimal insulation.

Part No	Description
V010130100	Optimus 300
V010140100	Optimus 400
V010150100	Optimus 500
V010160200	Optimus 600



ISOLATOR ELECTRODE HOLDER



- Made from high copper alloy casings with glass filled thermoplastic & thermoset components
- Electrode holder with locking mechanism
- Helps protect welder from open circuit voltage
- Safely reinsert electrode & position into tight areas
- Available in AF or HT style holders designed for 250 amps using 3/16" electrode max.

Part No	Description
L01535	AF Style with 12ft (3.6 m) cable & LDP-50 male connector
L01565	HT Style with 12ft (3.6 m) cable & LDP-50 male connector



INDEPENDENT WHOLESALE WELDING SUPPLY

Ph: 02 8834 2400 Fax: 02 8834 2498 Email: iwws@iwws.net Website: www.iwws.net