



CLOTH

- Abrasive Cloth
- 180 Grit
- Waterproof
- Premium grade
- Open mesh for all projects.



Part No	Description
79720	Abrasive Cloth 180 Grit



- Sand Cloth
- 120 Grit
- Water resistant
- Closed cloth for a quality finish.
- Aluminium oxide coating.

Part No	Description
79722	Sand Cloth 120 Grit

WIPES



- Great for job sites where water isn't available.
- Dispensing system prevents product from drying out if left open.
- Single towel dispensing and tear off.
- Lemon-lime scent.
- Patented wipe fabric, absorbs dirt and grime.

- Dual-surface towel.
 - One side smooth for wiping.
 - One side with Grime busting fibres for scrubbing.
- Large 10" x 12" wipe; 70 sheets per tub.
- Environmentally friendly.

Part No	Description
72405	Hand Lifter Wipes 70 pieces

LA-CO® PIPE THREAD SEALANT

Pipe Thread Sealant for Oxygen



- PTFE thread sealant specifically formulated for oxygen services.
- Each batch tested to ASTM G-72.
- Pressure: to 2,600 PSI (180 BAR)
- Sealing temperature: -196°C to 232°C

Part No	Description
42805	Sealant for Oxygen

Pipe Thread Tape



- Thickness 3 mils.
- Premium grade, high density.
- Provides a highly resistant seal on pipe threads for all types of services.
- Suitable for use with solvents, chemicals and oxygen.
- Non toxic
- Sealing temperature: -268°C to 260°C
- Pressures up to 10,000 psi.

Part No	Description
44080	Slic Tite Tape

Pipe Thread Sealant Paste



- Contains PTFE for greater sealing power.
- Use on metal, PVC, CPVC and ABS plastic pipe threads.
- For sealing water, air, steam, natural gas, LPG gas, refrigerants, ammonia, gasoline, ethanol and oil.
- Sealing temperature: -46°C to 260°C
- Safe, nontoxic, non-drying.

Part No	Description
41209	Paste Slic Tite Brush in Cap

Anaerobic Pipe Thread Sealant



- Contains PTFE for a positive seal.
- Sealing temperature: -54°C to 204°C
- Will not shrink, crack or shred.
- Provides an instant 1000 psi seal.
- Ideal for threads in heavy vibration areas such as compressors and reciprocating equipment.

Part No	Description
49050	Anaerobic Sealant

GAS LEAK DETECTOR



- High-visibility fluorescent colour shows brightly, even in dimly lit places.
- For use on CSST systems.
- Noncorrosive, nontoxic.
- High viscosity allows use on vertical surfaces.
- Safe for oxygen.
- Temperature range: -9°C to 93°C

Part No	Description
32844	Leak Detector for Gas 236 ml

HAND CLEANER



- Greaseless, waterless hand cleaner.
- Powerful, yet gentle for removing grime, paint, grease ink and oil.
- Removes difficult animal and chemical odours from hands.

Part No	Description
72412	Waterless Hand Cleaner



INDEPENDENT WHOLESALE WELDING SUPPLY

Ph: 02 8834 2400 Fax: 02 8834 2498 Email: iwws@iwws.net Website: www.iwws.net

LA-CO[®] FLUX PASTE


LA-CO Regular Flux is a water soluble flux. This all-weather flux is the ultimate flux for all copper soldering.

- Super detergent action cleans as it solders.
- Water soluble for faster flushing from pipe lines.
- Non- acid, non-toxic, lead free
- All weather, can be used in hot and cold climates.
- Contains no zinc chloride.
- For use on copper, brass, galvanised iron, lead zinc, tin, silver, nickel, mild steel, terne plate & malleable iron.



Part No	Description
22101	Flux Paste 56 gr
22104	Flux Paste 113 gr
22194	Flux Paste Brush in Cap 113 gr

Aluminium Flux Paste



- Solders aluminium at low temperature.
- Use soldering iron or torch with solder to safely solder aluminium below its melting point.
- Melt point for solder is 198°C.
- Works well with tin silver 94/4, 94/6, 95/5, 60/40, 40/60 and 50/50 solders.

Part No	Description
22407	Aluminium Paste Flux 450 gr

Aluminium Flux Paste & Solder Kit

- Complete repair kit containing solder.
- Solders aluminium easily.
- Also solders aluminium to copper.
- 90/10 mixture of tin and zinc.
- Melt point for solder is 198°C.
- Low temperature high tensile strength.
- For repairing aluminium evaporators and tubing, ducts and gutters.
- Resists electrolytic action between aluminium and copper connections.



Part No	Description
36474	Aluminium Paste Flux & Solder Kit 28 gr



INDEPENDENT WHOLESALE WELDING SUPPLY

Ph: 02 8834 2400 Fax: 02 8834 2498 Email: iwws@iwws.net Website: www.iwws.net