



THE ISOLATOR



The "ISOLATOR" Lenco's new "Patent Pending" Electrode Holder that is designed to create a safer working environment for today's welder when used as recommended.

The welder, with a simple pull of the welding cable, can engage the locking mechanism disconnecting the cable from the electrode holder.

The action protects the welder from OCV that is inherent in all SMAW stick welders.


When the "ISOLATOR" locking mechanism is engaged the welder is able to insert an electrode, position the electrode into tight difficult areas, or lay the holder down.

By pressing the button on the handle current is reconnected and the welder is ready to strike an arc.

Part No	Description
L01535	AF Style Isolator IS-25 with 12 FT Cable
L01565	HT Style Isolator ISH-25 with 12 FT Cable


PLUNGER DISENGAGED FROM LOWER JAW - OPEN CIRCUIT

PULL ON CABLE UNTIL BUTTON ENGAGES CATCH, WHICH HOLDS PLUNGER IN RETRACTED POSITION



PLUNGER ENGAGED WITH LOWER JAW - CLOSED CIRCUIT

PRESS CATCH TO RELEASE PLUNGER, WHICH ENGAGES LOWER JAW



CONICAL SURFACES ARE HELD TOGETHER BY SPRING PRESSURE WHICH ALLOWS WELDING CURRENT TO FLOW THROUGH ELECTRODE HOLDER



INDEPENDENT WHOLESALE WELDING SUPPLY

Ph: 02 8834 2400 Fax: 02 8834 2498 Email: iwws@iwws.net Website: www.iwws.net